

NLB1000

Barcode laser scanner

RS232

Keyboard Wedge

 USB (VCP)

+ Related products

RLB1000

- Stationary device
- Barcode raster laser scanner
- RS232, USB (VCP)
- IP 54, Metal diecast

NFT7175

- Stationary device
- Barcode CCD scanner
- RS232
- Sheet metal, 700 scans/sec

OPM5145

- Stationary device
- Omnidirectional laser scanner
- RS232, Keyboard Wedge, USB (HID/VCP)
- Zinc diecast



Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Communication

- RS232: DB9 PTF connector with external power supply
- USB: Ver. 1.1, VCP, USB-A connector

Power

- Voltage requirement: 5V \pm 10%
- Current consumption: Max. 500mA

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Polygon mirror
- Scan rate: 1000 scans/sec
- Trigger mode: Manual, multiple read, serial software trigger
- Reading pitch angle: -30 to 0°, 0 to +30°
- Reading skew angle: -60 to -7°, +9 to +60°
- Reading tilt angle: -25 to 0°, 0 to +25°
- Curvature: R>20 mm (EAN8), R>25 mm (EAN13)
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Depth of field: At PCS 0.9, Code 39
70 - 330 mm / 2.76 - 12.99 in (1.0 mm / 39 mil),
60 - 270 mm / 2.36 - 10.36 in (0.5 mm / 20 mil),
60 - 200 mm / 2.36 - 7.87 in (0.25 mm / 10 mil),
70 - 140 mm / 2.76 - 5.51 in (0.15 mm / 6 mil)

Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, GS1 DataBar (RSS), Code 128, GS1-128 (EAN-128), IATA, Industrial 2of5, Interleaved 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post
- 2D code: MicroPDF417, PDF417

Durability

- Temperature in operation: 0 to 45 °C / 32 to 113 °F
- Temperature in storage: -20 to 65 °C / -4 to 149 °F
- Humidity in operation: 5 - 90% (non-condensing)
- Humidity in storage: 5 - 90% (non-condensing)
- Ambient light immunity: Fluorescent 4,000 lx max, Direct sun 80,000 lx max, Incandescent 4,000 lx max
- Antistatic electricity: 15kV (non-destructive)
- Drop test: 0.75 m / 2.5 ft drop onto concrete surface
- Protection rate: IP 54

Physical

- Dimensions (w x h x d):
29 x 17 x 34 mm / 1.14 x 0.67 x 1.34 in
- Weight body: Ca. 30 g / 1.06 oz (excl. cable)
- Case: Metal diecast, Black

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

Sold separately

- Power supply 100-240V/0.5A, 50/60 Hz, 5W/2A (for RS232)

Models

- Interface versions: RS232, USB

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Villanova di Castenaso (BO)
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Brazil:** São Paulo
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** West Ryde

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM